

Technical parameters

Part number	NS	Capacity					Electric power* [kW]	Electrical connection	Weight total [kg]	Built-up area W x L [m]
		[PE]	Hydraulic load [m ³ /day]		Biological load [kg BOD ₅ /day]					
13031	60	25 - 60	3,8	9,0	1,5	3,6	0,6	400V / 50 Hz	650	2,3 x 5,3
13032	80	30 - 80	4,5	12,0	1,8	4,8	0,7	400V / 50 Hz	770	2,3 x 6,2
13033	100	40 - 100	6,0	15,0	2,4	6,0	0,9	400V / 50 Hz	895	2,3 x 7,7
13034	120	50 - 120	7,5	18,0	3,0	7,2	1,2	400V / 50 Hz	1 050	2,3 x 9,1
13035	160	65 - 160	9,8	24,0	3,9	9,6	1,5	400V / 50 Hz	1 210	2,3 x 10,7
13036	200	80 - 200	12,0	30,0	4,8	12,0	1,7	400V / 50 Hz	1 500	2,3 x 13,4
13037	240	100 - 240	15,0	36,0	6,0	14,4	2,1	400V / 50 Hz	2 035	5,1 x 9,1
13038	300	120 - 300	18,0	45,0	7,2	18,0	2,7	400V / 50 Hz	2 380	5,1 x 10,7

* Approximate value, the real consumption is dependent on the final technology

